

# P0123: Throttle Position Sensor (Main) Circuit High

## Wiring Diagram

Refer to "DTC P0122: Throttle Position Sensor (Main) Circuit Low".

## DTC Detecting Condition and Trouble Area

DTC detecting condition	Trouble area
Output voltage of throttle position sensor (main) is more than specified value for specified time. (1 driving detection logic)	<ul style="list-style-type: none"> <li>• Throttle position sensor (main) circuit</li> <li>• Electric throttle body assembly</li> <li>• ECM</li> </ul>

## DTC Confirmation Procedure

- 1) With ignition switch turned OFF, connect scan tool.
- 2) Turn ON ignition switch and clear DTC using scan tool.
- 3) Keep the accelerator pedal at idle position for 2 seconds.
- 4) Keep the accelerator pedal at fully depressed position for 2 seconds.
- 5) Repeat Step 3) and 4) for 3 times.

Step	Action	Yes	No
1	Was "Engine and Emission Control System Check" performed?	Go to Step 2.	Go to "Engine and Emission Control System Check".
2	Throttle position sensor and its circuit check 1) Connect scan tool to DLC with ignition switch turned OFF. 2) Turn ON ignition switch, check "TP Sensor 1 Volt" displayed on scan tool when accelerator pedal is idle position and fully depressed. Is displayed TP sensor value as described voltage in "Scan Tool Data"?	Intermittent trouble. Check for intermittent referring to "Intermittent and Poor Connection Inspection in Section 00".	Go to Step 3.

Step	Action	Yes	No
3	<p>ECM voltage check</p> <p>1) Disconnect connector from electric throttle body assembly with ignition switch turned OFF.</p> <p>2) Check for proper connection to electric throttle body assembly at "RED", "GRN" and "BLK" wire terminals.</p> <p>3) If OK, measure voltage between "RED" wire terminal of electric throttle body assembly connector and engine ground with ignition switch turned ON.</p> <p>Is voltage 4 – 6 V?</p>	Go to Step 5.	Go to Step 4.
4	<p>Wire harness check</p> <p>1) Disconnect connectors from ECM with ignition switch turned OFF.</p> <p>2) Check for proper connection of ECM connector at "C01-43" terminal.</p> <p>3) Measure voltage between "C01-43" terminal of ECM connector and engine ground with ignition switch turned ON.</p> <p>Is voltage 0 V?</p>	Substitute a known-good ECM and recheck.	"RED" wire is shorted to power circuit.
5	<p>Wire harness check</p> <p>1) Measure voltage between "GRN" wire terminal of electric throttle body assembly connector and engine ground with ignition switch turned ON.</p> <p>Is voltage 4 – 6 V?</p>	Go to Step 9.	Go to Step 6.
6	<p>Wire harness check</p> <p>1) Turn OFF ignition switch.</p> <p>2) Remove ECM from its bracket with ECM connectors connected.</p> <p>3) Check for proper connection of ECM connector at "C01-43" and "C01-54" terminals.</p> <p>4) If OK, measure voltage between "C01-54" terminal of ECM connector and engine ground with ignition switch turned ON.</p> <p>Is voltage 4 – 6 V?</p>	"GRN" wire is open or high resistance circuit.	Go to Step 7.

Step	Action	Yes	No
7	Wire harness check 1) Disconnect connectors from ECM with ignition switch turned OFF. 2) Measure resistance between "GRN" and "RED" wire terminals of electric throttle body assembly connector. Is resistance infinity?	Go to Step 8.	"GRN" wire is shorted to "RED" wire.
8	Wire harness check 1) Turn ON ignition switch. 2) Measure voltage between "C01-54" terminal of ECM connector and engine ground. Is voltage 0 V?	Substitute a known-good ECM and recheck.	"GRN" wire is shorted to power circuit.
9	Ground circuit check 1) Turn OFF ignition switch. 2) Measure resistance between "BLK" wire terminal of electric throttle body assembly connector and engine ground. Is resistance below 5 $\Omega$ ?	Go to Step 11.	Go to Step 10.
10	Ground circuit check 1) Remove ECM from its bracket with ECM connectors connected. 2) Check for proper connection of ECM connector at "C01-42" terminal. 3) Measure resistance between "C01-42" terminal of ECM connector and engine ground with ignition switch turned OFF. Is resistance below 5 $\Omega$ ?	"BLK" wire is open or high resistance circuit.	Faulty ECM ground circuit. If circuit is OK, substitute a known-good ECM and recheck.
11	Electric throttle body assembly check 1) Check throttle pedal position sensor referring to "Throttle Position Sensor Performance Check" under "Electric Throttle Body Assembly On-Vehicle Inspection in Section 1C". Is output voltage within specified value?	Substitute a known-good ECM and recheck.	Replace electric throttle body assembly.