


Instructions for Air Suspension Matching


[Function Description]

This function is to calibrate the height of each wheel. When the vehicle has following trouble, apply this function to resolve it.




[Instructions]


1. Turn on the ignition, start the engine, properly connect the connector, and then select AUDI car model version V27.90 or above.



2. Select [Special Function] -> [Air Suspension Matching].



3. After entry, first read and clear fault codes.



Diagnostic Trouble Code

AUDI V28.10 > Special Function>Air suspension matching

01437

Control position not adapted

No or Incorrect Basic Setting / Adaptation

Freeze Frame

Help

Related search

Audi

Report

VCI

Show Menu



AUDI V28.10 > Special Function>Air suspension matching

Clear Fault Codes



Audi

VCI

4. After clearing the fault code, it prompts as below. The prompted requirements must be satisfied before the operation.




5. First log in. Click [Login or Access Permission].



6. After successful login, select [001-match FL wheel height]. The air suspension will automatically adjust the height till balanced. When the prompted information changes from "Wait" to "FL Wheel", start to perform the height matching. Click "Input FL wheel height" button. If the input value is reasonable, it prompts the height value is saved

successfully. Otherwise, it will not be saved.



Active Test

Home

Print

Calendar

User

Export

AUDI V28.10 > Special Function>Air suspension matching

Name	Value	Unit
Current FL wheel height	000	mm
Information	Value	
Information	Wheel: F/Left	
Information	Enter	
Information	-	

Input FL wheel height

Audi

Refresh

Image

VCI

Window

Home

Back

Active Test

Home

Print

Calendar

User

Export

AUDI V28.10 > Special Function>Air suspension matching

Name	Value	Unit
Current FL wheel height	000	mm
Information		
Information		
Information		
Information		

Input FL wheel height

Enter a reasonable height value. Otherwise, the value may fail to be saved.

416

Cancel

OK

Input FL wheel height

Audi

Refresh


Image

VCI


Window

Home

Back



7. After [001-match FL wheel height] is successfully done, continue to perform [002-match FR wheel height]. Click "Input FR wheel height" to input a reasonable height value.



Active Test

Home

Print

Calendar

User

Export

AUDI V28.10 > Special Function>Air suspension matching

Name	Value	Unit
Current FR wheel height	000	mm
Information	Value	
Information	Wheel: F/Right	
Information	Enter	
Information	-	

Input FR wheel height

Audi

Refresh

Download

VCI

Window

Home

Back

Active Test

Home

Print

Calendar

User

Export

AUDI V28.10 > Special Function>Air suspension matching

Name	Value	Unit
Current FR wheel height	000	mm
Information		
Information		
Information		
Information		

Input FR wheel height

Enter a reasonable height value. Otherwise, the value may fail to be saved.

416

Cancel

OK

Input FR wheel height

Audi

Refresh


Download

VCI

Window

Home

Back



8. After [002-match FR wheel height] is successfully done, continue to perform [003-match RL wheel height] and [004-match RR wheel height]. Operation is same as stated in Step 7.
9. After completion of above four wheel height settings, perform [005-save all height values] to save the previously entered values. See below interfaces, and the input value is 1. If channel 5 is not done, the previously entered four height values will not be saved. After successful saving, it prompts the air suspension matching succeeded.

9:50 am

Show Menu

Home

Print

Report

User

Exit

AUDI V28.10 > Special Function>Air suspension matching

005-save all height values

Audi

Refresh

Download

VCI

Window

Home

Back

9:50 am

Active Test

Home

Print

Report

User

Exit

AUDI V28.10 > Special Function>Air suspension matching

Name	Value	Unit
Storage status of all height values	000	
Information	Value	
(no units)	1.00	
Information	Enter	
Information	-	

Save all height values

Audi

Refresh



Download


VCI

Window

Home

Back





10. After above operations, read fault codes again. It will prompt "No fault code". The fault indicator light will also go out. Matching succeeded.

