

## Instruction for the operation of Anti-Theft Key Matching - Add A Smart Key for 2016 Honda Civic

### Tested model

Honda CIVIC 2016, VIN: LVHFC1669G603\*\*\*\*\*

### Features

The process of key matching – Add a key.

### Requirements

**Product requirement:** X-431 IMMO PRO, X-431 IMMO PAD

**Software requirement:** Honda Anti-theft software V10.01 and above

### Notes

1. You must have an original key;
2. Before performing the operation, ensure that the vehicle battery voltage is not lower than 12V and the device has sufficient power;
3. During operation, strictly follow the device prompts to switch ignition OFF/ON;
4. During operation, strictly follow the device prompts to put the corresponding key in or outside the vehicle;
5. After the key registration completed, check whether all the keys normally open and close the doors and start engine normally.

### Steps

1. Turn off the ignition switch (if the ignition switch has been turned on), prepare all the keys, and connect the diagnostic device, enter the corresponding IMMO module, and select HONDA Anti-theft diagnostic software, as shown in Figure 1.



Figure 1

2. Select the menu **【Anti-Theft Key Matching】**, the software will automatically detect the Anti-theft type and display the corresponding function menu, as shown in Figure 2.




Figure 2

3. As described in above function introduction. Select the function **【Add A Honda Smart Key】**, as shown in Figure 3.




Figure 3

4. Turn the ignition switch to OFF, as shown in Figure 4.

**Note:** This operation will be performed more than once during operating, please perform by strictly following the prompts.




Figure 4

5. Take only one original keyless access remote into the vehicle, and remove all other keyless access remotes from the vehicle, as shown in Figure 5.




Figure 5

6. Turn the ignition switch to ON, as shown in Figure 6.




Figure 6

7. Countdown, please take all keyless remotes (keys) out of the vehicle within 100 seconds, as shown in Figure 7.




Figure 7

8. Countdown, please take just one new keyless remote (key) into the vehicle within 100 seconds, as shown in Figure 8.




Figure 8

9. Now start registration for this keyless access remote, as shown in Figure 9.




Figure 9

10. Turn the ignition switch to OFF, as shown in Figure 10.

**Note:** This operation will be performed more than once during operating, please perform by strictly following the prompts.




Figure 10

11. Turn the ignition switch to ON, as shown in Figure 11. Click OK for communicating, please wait for about 10 seconds.




Figure 11

12. Check whether the keyless access remote and immobilizer indicator light goes off. If it is not off, the matching failed; if it is off, continue to check whether the key matching is successful, as shown in Figure 12.




Figure 12

13. Turn the ignition switch to OFF, as shown in Figure 13.




Figure 13

14. Turn the ignition switch to ON, as shown in Figure 14.




Figure 14



15. Registration completed. Turn the ignition switch to OFF, as shown in Figure 15, 16.




Figure 15




Figure 16

16. Check the smart key, try to start Engine, lock and unlock doors, as shown in Figure 17.




Figure 17

17. Turn the ignition switch to ON. **Add A Smart Key completed.**

## Statement

The content of this document belongs to Shenzhen Launch. All rights reserved. Any individual or unit shall not quote or reprint without consent.